

# Standard Door Holders

Arguably the single most important fire safety mechanism, electromagnetic door holders guard against the lethal spread of toxic smoke and fumes - by far the greatest cause of death in fires.

The Vimpex EN 1155 approved standard range of door holders offers the installer a choice of mounting styles, holding power and installation accessories.

Mounted onto a fixed surface, these door holders ensure retention of the fire door by means of a smart metallic keeper plate. Interfaced with the fire alarm system, the door holders are de-energised as soon as the fire is detected thus releasing the door without the potentially harmful delay suffered by other types of devices.

## Features

- Supplied as standard with 200N holding force
- Attractive finish, featuring a strengthened cast back box
- Metal enclosure means no heat fatigue
- Available in 230 V ac and 24 V dc
- Flush mounted versions and units with a greater holding force also available
- Manual release button
- Approved to EN 1155 and CE marked

## Specification

Part Number:	Description	Rated Voltage	Nominal Current	Holding Force	Temperature Range	IP Rating	Door Closure Power Size	Weight
DH/S/24:	Surface DC	24 V dc	50 mA	200N	0-40°C	N/A	3 to 6	530g
DH/F/24:	Flush DC	24 V dc	50 mA	200N	0-40°C	N/A	3 to 6	530g
DH/S/230:	Surface AC	230 V ac	12 mA	200N	0-40°C	N/A	3 to 6	530g
DH/F/230:	Flush AC	230 V ac	12 mA	200N	0-40°C	N/A	3 to 6	530g

## Spares & Accessories

- DH/KP/STND: Standard Swivel Keeper Plate
- DH/FB: Floor Mounting Bracket
- DH/KP/LP/500: Low Profile Keeper Plate
- DH/CHO: Keeper Plate with Extension Chain and Rubber Ring

## Vimpex Limited

Star Lane, Great Wakering  
Essex SS3 0PJ England  
Tel: +44 (0) 1702 216999  
Fax: +44 (0) 1702 216699  
E-mail: sales@vimpex.co.uk  
[www.vimpex.co.uk](http://www.vimpex.co.uk)



## Installation

Dimensions (mm)

